

2SM



2SM Case sealer for inner cartons

Productivity Focus

Performance operating speed of 20 meters per minute

Easy Maintenance

Easy access to motors, electrical components and belts for maintenance

Production Versatility

Wide range of supported case sizes to meet customer requirements

Operator Friendly

Easy to operate with simple controls and intuitive tape roll replacement

2SM

Case sealer for inner cartons



Features and Benefits

- Ideal for case sealing of smaller/inner cartons
- Twin mast column for greater stability during operation
- Spring loaded top drive set for smooth flow and gentle handling of delicate cartons
- Uniform and controlled pressure during taping
- Consistent tape overlap
- Telescopic legs for height adjustment
- Quick and simple adjustment for varying carton sizes



Utility Requirements

Power	230 VAC, 1 Phase, 50 Hz
Consumption	0.36 KW
Pneumatic	NA

Case Dimensions

Length	80mm to Unlimited
Width	90mm to 300mm
Height	80mm to 300mm
Weight	1 to 20 Kg
Carton Ply	Minimum 3 Ply

Technical Specifications

Tape Head	Standard (1.5", 2")
Tape Roll Length	65 M / 650 M / 1000 M
Machine Length	830mm
Machine Width	670mm
Machine Height	1320mm
Weight	110 Kg
Drive Motor	0.25 HP, 2 No.
Throughput	Up to 25 cartons / minute