CW











pac

bundle

unitize

warehouse transport



Productivity Focus

Wrap individual cartons at a convenient height for the operator.

Easy Maintenance

Easy access to motors and electrical components for maintenance

Simplified Integration

Requires minimal set-up and less floor space than comparable wrappers

Operator Friendly

Easy to operate with simple controls and intuitive stretch film replacement



CW

Carton wrapping machine

PRODUCTS SERVICES INTEGRATION AUTOMATION pack bundle unitize warehouse transport

Features and Benefits

- Highly reliable AC drives and motors
- Powered pre-stretch variable up to 300%
- Independent film tension adjustment for wrapping both lightweight and heavy cartons
- PLC controlled function with digital display of stretch percentage and weight of the film consumed per carton
- Convenient operating height
- Top holding attachment for securing cartons in place while wrapping



Utility Requirements / Electrical		
Power	230 VAC, 1 Phase, 50 Hz, 16 A	
Consumption	2.0 KW	

Carton Dimensions		
Length	200mm to 750mm	
Width	200mm to 500mm	
Height	200mm to 500mm	
Diagonal	910mm	
Weight	200 Kg Maximum	

Machine Dimensions	
Length	1515mm
Width	910mm
Height	1630mm
Weight	400 Kg

Technical Specifications	
Turntable Speed	VFD Control
Turntable Diameter	910mm
Turntable Rollers	Tapered Bearing
Turntable Drive	Gear (worm) Reducer
Turntable Motor	0.5 HP, 415 VAC, 3 Ph, 50 Hz
Pre-Stretch Type	Powered
Film Stretch	Variable up to 300%
Film Roll Width	250mm to 500mm
Film Roll Diameter	254mm (10") Maximum
Core Size	76.2mm (3")
Elongation	Up to 300%

